14.01	TWO-WAY VIDEO AND VOICE	37	.With continuously rotating element
	COMMUNICATION (E.G.,	38	.Multiple channels
14.02	VIDEOPHONE) .Over wireless communication	39	.With observer selected field of
14.02			view
14.03	.User interface (e.g., touch	40	HOLOGRAPHIC
14 04	screen menu)	41	.Color TV
14.04	Operating with other appliance	42	STEREOSCOPIC
14 05	(e.g., TV, VCR, FAX, etc.)	43	.Signal formatting
14.05	.Remote control	44	.Pseudo
14.06	.Answering machine	45	.Endoscope
14.07	.Display arrangement (e.g.,	46	.Picture signal generator
14 00	multiscreen display)	47	Multiple cameras
14.08	.Conferencing (e.g., loop)	48	
14.09	Conferencing with multipoint		More than two cameras
1 4 1	control unit	49	Single camera with optical path division
14.1	Motion image conferencing	Γ0	
14.11	.Switching	50	Single camera from multiple
14.12	.Transmission control (e.g.,	г1	positions
	resolution or quality)	51	.Stereoscopic display device
14.13	Compression or decompression	52	More than two display devices
14.14	Still frame (e.g., freeze	53	Viewer attached
	frame)	54	Single display with optical
14.15	Field or frame difference		path division
	(e.g., moving frame)	55	Separation by time division
14.16	.User positioning (e.g.,	56	With alternating shutters
	parallax)	57	With alternating polarization
21	PLURAL TRANSMITTER SYSTEM	58	Separation by polarization
	CONSIDERATIONS (E.G.,	59	Separation by lenticular
	INTERFERENCE REDUCTION)		screen
22	SLOW SCANNING TRANSMISSION (E.G.,	60	Separation by color (i.e.,
	STILL FRAME)		anaglyphic)
23	.Color TV	61	SPECIAL APPLICATIONS
24	PLURAL STILL IMAGES OVER	62	.Aid for the blind
	CONVENTIONAL CHANNEL	63	Image magnifying
25	IMAGE FALSIFICATION TO IMPROVE	64	.Combined electronic sensing and
	VIEWER PERCEPTION OF SELECTIVE		photographic film cameras
	OBJECT (E.G., MOVING OBJECT OR	65	.With endoscope
	TARGET)	66	Dental
26	.Contour generator	67	Laser
27	.Quantizer	68	Illumination
28	.Selective contrast expander	69	Controlled by video signal
29	.False color	70	Color sequential illumination
30	Hue expander	71	Color TV
31	BACK SCATTER REDUCTION	72	Plural endoscopes
32	PSEUDO COLOR		interchangeable
33	.Multispectral to color	73	External camera
	conversion (e.g., infrared and	74	With additional adjunct (e.g.,
	visible, infrared bands, etc.)		recorder control, etc.)
34	.Including intensity to color	75	Adaptor or connector
	conversion (e.g., colorizer,	76	Physical structure of circuit
	etc.)		element
35	PSEUDO BLACK AND WHITE	77	.Human body observation
36	PANORAMIC	78	Eye

79	.Microscope	125	.Flaw detector
80	Electronic	126	Of electronic circuit chip or
81		120	board
		127	
82	.Hazardous or inaccessible	127	Of transparent container or
83	Furnace (e.g., nuclear reactor,		content (e.g., bottle, jar,
	etc.)	100	etc.)
84	Pipeline	128	Of surface (e.g., texture or
85	Borehole	100	smoothness, etc.)
86	.Manufacturing	129	By comparison with reference
87	Electronic circuit chip or		object
	<pre>board (e.g., positioning)</pre>	130	With stored representation of
88	Web, sheet or filament		reference object
89	Agricultural or food production	131	With specific illumination
90	Welding		detail
91	Sorting, distributing or	132	With strobe illumination
	classifying	133	With circuit detail
92	Quality inspection	134	Including line to line
93	Color TV		comparison
94	Position detection	135	.Object or scene measurement
95	Alignment or positioning	136	Projected scale on object
96	.Film, disc or card scanning	137	Scale on camera target
97	Motion picture film scanner	138	Pulse or clock counting
98	Mechanical optical scanning	139	Multiple cameras on baseline
99			(e.g., range finder, etc.)
100	Flying spot scanner	140	Distance by apparent target
	Flying spot scanner	110	size (e.g., stadia, etc.)
101	Color TV	141	By cursor coordinate location
102	Intermittent film movement	142	With camera and object moved
103	With modification of scanner	112	relative to each other
	sweep	143	Observation of or from a
104	Color TV	143	
105	Intermittent film movement		<pre>specific location (e.g., surveillance)</pre>
106	With modification of scanner	144	•
	sweep		Aerial viewing
107	With record location	145	With linear array
108	Flying spot scanner	146	With rotating reflector
109	Color TV	147	With transformation or
110	Slide		rectification
111	Color TV	148	Vehicular
112	Microfilm	149	Traffic monitoring
113	.Navigation	150	Point of sale or banking
114	Remote control	151	Camera concealment
115	Head-up display	152	Intrusion detection
116	Direction finding or location	153	Using plural cameras
	determination	154	Motion detection
117	Aircraft or spacecraft	155	Motion detection
118	Land vehicle	156	Access control
119	Program control (e.g., path	157	Sporting event
119	guidance, etc.)	158	Portable
100	_	159	Plural cameras
120	Farm vehicle	160	Reading meter or data printer
121	Simulator	161	.Object comparison (e.g., remote
122	Visibility (e.g., fog, etc.)	T V T	verification of signature,
123	Aircraft or spacecraft		etc.)
124	Ship		200. /

162	RESPONSIVE TO NONVISIBLE ENERGY	207.99	CAMERA, SYSTEM AND DETAIL
163	.Sonic or ultrasonic	207.1	.Camera connected to computer
164	.Infrared	207.11	Computer can control camera
165	Pyroelectric	207.2	.Camera connected to printer
166	With linear array	208.99	.Camera image stabilization
167	With rotating reflector	208.1	Electrical motion detection
168	With rotating reflector	208.2	Mechanical motion detection
169	OBJECT TRACKING		(gyros, accelerometers, etc.)
170	.Using tracking gate	208.3	Differentiating unintentional
171	Centroidal tracking		from purposeful camera
172	.Centroidal tracking		movement (pan, tilt)
173	CATHODE-RAY TUBE BURN-IN	208.4	Motion correction
	PREVENTION	208.5	Including both electrical and
174	.Camera		mechanical correcting devices
175	CAMERA WITH BUILT-IN TEST SIGNAL	208.6	Electrical (memory shifting,
	GENERATOR, TEST PATTERN, OR		electronic zoom, etc.)
	ADJUSTING ADJUNCT	208.7	Mechanical
176	.Setup	208.8	Variable angle prisms
177	DISPLAY OR RECEIVER WITH BUILT-IN	208.11	Optics, lens shifting
	TEST SIGNAL GENERATOR, TEST	208.12	Combined with other camera
178	PATTERN, OR ADJUSTING ADJUNCT .Setup		operations (e.g., autofocus or autoexposure details)
179	Color match comparator	208.13	Motion correction plus
180	MONITORING, TESTING, OR MEASURING	200.13	resolution enhancement
181	.Test signal generator	208.14	Object tracking
182	Chroma or color bar	208.15	Warning/indicator
183	VITS or ILTS	208.16	Changing camera function based
184	.Monitor	200.10	on motion detection (mode,
185	Combined plural functions		power supply)
103	(e.g., picture and waveform	209.99	.With flying spot scanner
	monitor)	210.99	For color scanning
186	Vectorscope	211.99	.Remote control
187	.Testing of camera	211.1	Communication methods
188	Using test chart	211.2	Wireless
189	.Testing of image reproducer	211.3	Network (master/slave, client
190	Alignment-manufacturing	211.3	or server, etc.)
191	Display photometry	211.4	Control devices
192	Display photometry .Transmission path testing	211.5	Multiplexed or other embedded
193	Signal to noise ratio	211.3	control signals
194	Synchronization (e.g., H-sync to	211.6	Preprogrammed or stored
174	subcarrier)		control instructions
195	MECHANICAL OPTICAL SCANNING	211.7	Electromechanical controls
196	.Color TV		(joystick, trackball, mouse,
197	.With fiber optics		etc.)
198	.By acoustic wave	211.8	Monitor used to control remote
199	.Moving aperture		camera
200	Drum or belt	211.9	Camera characteristics
201	Multiple scanning elements		affecting control (zoom angle,
201	Murtiple scanning elements .Moving lens or refractor		distance to camera time
202	.Moving reflector		delays, weight, etc.)
203	Helical element	211.11	Plural cameras being controlled
204	Vibrating or oscillating	211.12	Video teleconferencing
205	SPECIAL SCANNING (E.G., SPIRAL,		(including access or
200	RANDOM, ZIGZAG)		authorization)

011 10		004	
211.13	Monitor (including for	234	Details of luminance signal
	controlling camera)		formation in color camera
211.14	Camera located remotely from	235	With means for providing high
	image processor (i.e., camera		band and low band luminance
0.1 = .1	head)		signals
215.1	.With streak device	236	Using distinct luminance
216.1	.Low light level		image sensor
217.1	With image intensifier	237	For single sensor type camera
218.1	.Unitary image formed by		supplying plural color signals
	compiling sub-areas of same	238	Using distinct luminance image
	scene (e.g., array of cameras)		sensor
219.1	.Swing driven	239	Camera and video special
220.1	.Still and motion modes of		effects (e.g., subtitling,
	operation		fading, or merging)
221.1	Exposure control	241	Including noise or undesired
222.1	.Combined image signal generator		signal reduction
	and general image signal	242	Color TV
	processing	243	Dark current
223.1	Color balance (e.g., white	244	With control of sensor
	balance)		temperature
224.1	Dependent upon operation or	245	Using dummy pixels
	characteristic of iris, flash,	246	Defective pixel (e.g., signal
	lens, or filter)		replacement)
225.1	With means for preventing	247	With memory of defective
	colored object from effecting		pixels
	color balance	248	Smear
226.1	Including flicker detection	249	In charge coupled type sensor
	(e.g., fluorescent)	250	In charge coupled type sensor
227.1	With ambient light sensor	251	Shading or black spot
228.1	Responsive to output signal		correction
229.1	Combined automatic gain control	252	With transition or edge
	and exposure control (i.e.,		sharpening (e.g., aperture
	sensitivity control)		correction)
230.1	Readout of solid-state image	253	Color TV
	sensor considered or altered	254	Gray scale transformation
231.99	With details of static memory		(e.g., gamma correction)
	for output image (e.g., for a	255	Amplitude control (e.g.,
	still camera)		automatic gain control)
231.1	Available memory space	256	Color TV (e.g., saturation)
	detection	257	With DC level control
231.2	Image file management	258	With bias illumination
231.3	Storage of additional data	259	Combined with color
231.4	Audio	237	separating optical system
231.5	Time or date, annotation	260	For single scanning device
231.6	Processing or camera details	200	color camera
231.7	Detachable	261	Plural bias illuminators
231.8	Multiple detachable memories	262	
231.9	Details of communication	202	.With plural image scanning devices
231.7	between memory and camera	262	
240.99	Zoom	263	Color imagery registration
240.99	Using both optical and	264	Scanning devices offset in the
710.T	electronic zoom	265	image plane
240.2	Electronic zoom	265	Each supplying only one color
240.2			signal
∠ 1 0.3	Optical zoom		

266	.With single image scanning	302	X - Y architecture
	<pre>device supplying plural color signals</pre>	303	With charge transfer type output register
267	Separate complete images on	304	With charge transfer type
	face of pickup device		selecting register
268	Color sequential	305	With interlacing
269	With color sequential	306	Charge injection device (CID)
	illumination	307	Photosensitive switching
270	With moving color filters	30.	transistors or "static
271	Four or more color types		induction" transistors
272	Solid-state multicolor image	308	Including switching transistor
	sensor		and photocell at each pixel
273	With color filter or operation		site (e.g., "MOS-type" image
	according to color filter		sensor)
274	Having overlapping elements	309	Exclusively passive light
275	Staggered or irregular		responsive elements in the
	elements		matrix
276	Including transparent	310	With diode in series with
	elements		photocell
277	With three or more colors	311	Charge-coupled architecture
278	Based on more than four	312	With timing pulse generator
	colors	313	With bias charge injection
279	Based on four colors	314	With excess charge removal
280	Based on three colors		(e.g., overflow drain)
281	X-Y architecture	315	With staggered or irregular
282	Charge coupled architecture		photosites or specified
283	With multiple output		channel configuration
200	registers	316	Charges transferred to opposed
284	Cathode-ray tube		registers
285	Phase separable signals	317	Field or frame transfer type
286	With indexing	318	With recirculation of charge
287	Conductive grid at target	319	Charges alternately switched
288	Index elements outside of		from vertical registers into
200	image area		separate storage registers; or
289	Frequency separable signals		having vertical transfer gates
290	Specified optical filter	320	Interline readout
270	arrangement	321	Using multiple output
291	Combined with grating, lens		registers
	array, or refractor	322	Interline readout
292	Having diagonally arranged	323	Using multiple output
	stripes		registers
293	Interdigital signal	324	Line transfer type
	electrodes	325	.Cathode-ray tube
294	.Solid-state image sensor	326	Automatic beam focusing or
295	Time delay and integration mode		alignment
	(TDI)	327	Automatic beam current control
296	Electronic shuttering	328	Remanent image erasure
297	Accumulation or integration	329	With emissive target or
	time responsive to light or		<pre>photocathode (e.g., orthicon)</pre>
	signal intensity	330	Dissector tube
298	In charge coupled type image	331	With photoconductive target
	sensor		(e.g., vidicon)
299	With overflow gate or drain	332	.Array of photocells (i.e.,
300	With amplifier		nonsolid-state array)
301	Pixel amplifiers		

333.01	.With electronic viewfinder or	357	Servo unit structure or
222 00	display monitor	250	mechanism
333.02	With display of additional	359	Fiber optics
222 22	information	360	Lens or filter substitution
333.03	Including display of a frame	361	Automatic
	and line of sight	362	Exposure control
	determination	363	Automatic control of iris,
333.04	Including warning indication		stop, or diaphragm
333.05	Display of multiple images	364	Based on image signal
	(e.g., thumbnail images, etc.)	365	Contrast
333.06	Movable or rotatable unit	366	Based on ambient light
333.07	Detachable	367	Periodic shuttering
333.08	Including optics	368	Rotary
333.09	With optical viewfinder (e.g.,	369	Changing viewing angle via
	correction for parallax, etc.)		optics
333.1	With projector function	370	.With object or scene
333.11	Use for previewing images		illumination
	(e.g., variety of image	371	Flash or strobe
	resolutions, etc.)	372	.Power supply
333.12	Modification of displayed image	373	.Support or housing
333.13	Power saving mode	374	For internal camera components
335	.Optics	375	For specified accessory
336	Color separating optics	376	Portable or hand-held
337	Prism arrangement	377	CATHODE-RAY TUBE DISPLAY
338	With dichroic layer or air		EXCESSIVE VOLTAGE CONTROL
	gap between prism sections	378	.With disabling
339	Exclusively dichroic elements	379	CATHODE-RAY TUBE DISPLAY
340	With optics peculiar to solid-		AUTOMATIC BLACK LEVEL BIAS
340	With optics peculiar to solid- state sensor		AUTOMATIC BLACK LEVEL BIAS CONTROL
340 341		380	
	state sensor	380	CONTROL
341	<pre>state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF,</pre>	380 381	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining
341 342	<pre>state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)</pre>	381	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color
341 342 343	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexing		CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration
341 342 343 344	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switching	381	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the
341 342 343 344 345	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus control	381 382	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer
341 342 343 344	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing	381 382 383	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM
341 342 343 344 345 346	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarm	381 382 383 384.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM
341 342 343 344 345	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection	381 382 383	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single
341 342 343 344 345 346	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris control	381 382 383 384.1 385.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel
341 342 343 344 345 346 347	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active ranging	381 382 383 384.1 385.1 386.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single
341 342 343 344 345 346 347 348 349	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signal	381 382 383 384.1 385.1 386.1 387.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction
341 342 343 344 345 346 347	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or	381 382 383 384.1 385.1 386.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction .Multiple channel (e.g., plural
341 342 343 344 345 346 347 348 349 350	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imager	381 382 383 384.1 385.1 386.1 387.1 388.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction .Multiple channel (e.g., plural carrier)
341 342 343 344 345 346 347 348 349	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or	381 382 383 384.1 385.1 386.1 387.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction .Multiple channel (e.g., plural carrier)Including one conventional or
341 342 343 344 345 346 347 348 349 350	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error	381 382 383 384.1 385.1 386.1 387.1 388.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signal	381 382 383 384.1 385.1 386.1 387.1 388.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction .Multiple channel (e.g., plural carrier)Including one conventional or compatible channel (e.g., two channel NTSC systems)
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detection	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reduction
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detectionBy detecting contrast	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining colorVariable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channelColor televisionData rate reduction .Multiple channel (e.g., plural carrier)Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reductionSpecified color signal
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detectionBy detecting contrastBy analyzing high frequency	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1 390.1 391.1 392.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reduction Specified color signal Sub-Nyquist sampling
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detectionBy detecting contrastBy analyzing high frequency component	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reduction Specified color signal Sub-Nyquist sampling Direct coding of color
341 342 343 344 345 346 347 348 349 350 351 352 353 354 355	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detectionBy detecting contrastBy analyzing high frequency componentPlural high frequencies	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1 390.1 391.1 392.1 393.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reduction Specified color signal Sub-Nyquist sampling Direct coding of color composite signal
341 342 343 344 345 346 347 348 349 350 351	state sensorOptical viewfinderWith frequency selective filter (e.g., IR cut, optical LPF, etc.)Optical multiplexingOptical path switchingFocus controlWith display of focusing condition or alarmWith zoom position detection or interrelated iris controlUsing active rangingUsing image signalWith auxiliary sensor or separate area on imagerWith oscillation of lens or sensor to optimize error signalWith motion detectionBy detecting contrastBy analyzing high frequency component	381 382 383 384.1 385.1 386.1 387.1 388.1 389.1 390.1 391.1 392.1	CONTROL CATHODE-RAY TUBE DISPLAY BEAM CURRENT CONTROL .With beam energy determining color Variable depth of penetration of electron beam into the luminescent layer MODULAR IMAGE DISPLAY SYSTEM BANDWIDTH REDUCTION SYSTEM .Plural video programs in single channel Color television Data rate reduction .Multiple channel (e.g., plural carrier) Including one conventional or compatible channel (e.g., two channel NTSC systems) .Data rate reduction Specified color signal Sub-Nyquist sampling Direct coding of color

396.1	Including luminance signal	426.1	.Format type
397.1	Using separate coders for	427.1	Including frequency folding
	different picture features		(e.g., subsampling)
	(e.g., highs, lows)	428.1	Spotwobble (e.g., pixels from
398.1	Subband encoding (e.g., low		plural lines form single
	horizontal/low vertical	400 1	transmitted line)
	<pre>frequency, low horizontal/high vertical frequency)</pre>	429.1	Including video-related information
399.1	Picture feature dependent	430.1	Using two or more frames
3,7,1	sampling rate or sample	431.1	Motion adaptive
	selection	432.1	Added video information in
400.1	Involving hybrid transform and	132.1	standard channel format
	difference coding	433.1	Including additional
401.1	With prior difference coding	100.1	modulation of picture carrier
402.1	Including motion vector		(e.g., quadrature)
403.1	Involving transform coding	434.1	Including information in sync,
404.1	Adaptive		blanking, or overscan
405.1	Sampling	435.1	During vertical blanking
406.1	Normalizer		interval
407.1	Motion	436.1	Including use of a subcarrier
408.1	Transformed sample selection	437.1	Individual processing of
	(e.g., hierarchical sample		different parts of image
	selection)		frequency band (e.g., sum and
409.1	Involving difference		difference, high band/low
	transmission (e.g.,	420 1	band)
410 1	predictive)	438.1	.Individual processing of
410.1	Involving both base and		different parts of image frequency band (e.g., sum and
411.1	differential encodingPlural predictors		difference, high band/low
412.1	Including temporal predictor		band)
112.1	(e.g., frame difference)	439.1	.Frame field or line dropping
413.1	Including motion vector		followed by time expansion and
414.1	Involving pattern matching		time compression
415.1	Including temporal prediction	440.1	.Scan rate variation
415.1	Including temporal prediction (e.g., frame difference)	440.1 441	.Scan rate variation FORMAT CONVERSION
416.1	(e.g., frame difference)		
		441	FORMAT CONVERSION
416.1	<pre>(e.g., frame difference)Including motion vector</pre>	441	FORMAT CONVERSION .Involving polar to Cartesian or
416.1 417.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matching</pre>	441 442	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g.,
416.1 417.1 418.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matching</pre>	441 442 443	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)
416.1 417.1 418.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by</pre>	441 442 443	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal
416.1 417.1 418.1 419.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullness</pre>	441 442 443	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards
416.1 417.1 418.1 419.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block coding</pre>	441 442 443 444 445	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios
416.1 417.1 418.1 419.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matching</pre>	441 442 443 444 445 446	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace
416.1 417.1 418.1 419.1 420.1 421.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing</pre>	441 442 443 444 445	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker
416.1 417.1 418.1 419.1 420.1 421.1	 (e.g., frame difference) Including motion vector Involving pattern matching Involving pattern matching Coding element controlled by buffer fullness Involving block coding Involving minimum, maximum, or average of block Involving pattern matching Arrangements for multiplexing one video signal, one or more 	441 442 443 444 445 446 447	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating
416.1 417.1 418.1 419.1 420.1 421.1	 (e.g., frame difference) Including motion vector Involving pattern matching Involving pattern matching Coding element controlled by buffer fullness Involving block coding Involving minimum, maximum, or average of block Involving pattern matching Arrangements for multiplexing one video signal, one or more audio signals, and a 	441 442 443 444 445 446	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g.,
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1	 (e.g., frame difference) Including motion vector Involving pattern matching Involving pattern matching Coding element controlled by buffer fullness Involving block coding Involving minimum, maximum, or average of block Involving pattern matching Arrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signal 	441 442 443 444 445 446 447	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist sampling</pre>	441 442 443 444 445 446 447 448	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist samplingAdaptive</pre>	441 442 443 444 445 446 447	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)Including nonstandard signal
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1 424.1 424.2 425.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist samplingAdaptiveAssociated signal processing</pre>	441 442 443 444 445 446 447 448	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)Including nonstandard signal detection
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist samplingAdaptiveAssociated signal processingInvolving error detection or</pre>	441 442 443 444 445 446 447 448	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)Including nonstandard signal detectionSpecified chrominance
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1 424.1 424.2 425.1 425.2	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist samplingAdaptiveAssociated signal processingInvolving error detection or correction</pre>	441 442 443 444 445 446 447 448	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)Including nonstandard signal detection
416.1 417.1 418.1 419.1 420.1 421.1 422.1 423.1 424.1 424.2 425.1	<pre>(e.g., frame difference)Including motion vectorInvolving pattern matchingInvolving pattern matchingCoding element controlled by buffer fullnessInvolving block codingInvolving minimum, maximum, or average of blockInvolving pattern matchingArrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signalSub-Nyquist samplingAdaptiveAssociated signal processingInvolving error detection or</pre>	441 442 443 444 445 446 447 448	FORMAT CONVERSION .Involving polar to Cartesian or vice versa .Involving both line number and field rate conversion (e.g., PAL to NTSC)Specified chrominance signal .Conversion between standards with different aspect ratios .Progressive to interlace .Field rate type flicker compensating .Line doublers type (e.g., interlace to progressive IDTV type)Including nonstandard signal detectionSpecified chrominance processing (e.g., Y/C

452	Motion adaptive	487	.Broadband (e.g., occupying two
453	.Specified chrominance processing		adjacent channels or parts
454	PAL to NTSC or vice versa		thereof)
455	In which simultaneous signals	488	.Specified color signal format
433	5	489	Time division multiplexing of
	are converted into sequential	409	
	signals or vice versa		luminance and chrominance
456	Field or frame sequential to		(e.g., MAC)
	simultaneous	490	Field or frame sequential
457	Frequency change of subcarrier		systems
458	.Changing number of lines for	491	Simultaneous and sequential
	standard conversion		(e.g., SECAM)
459	.Changing number of fields for	492	Simultaneous signals
107	standard conversion	493	Luminance plus dual-phase
460	DIVERSE DEVICE CONTROLLED BY	100	modulated color carrier
400		494	
	INFORMATION EMBEDDED IN VIDEO		Dot sequential
	SIGNAL	495	.Of sync signal
461	NONPICTORIAL DATA PACKET IN	496	Color
	TELEVISION FORMAT	497	FLUTTER OR JITTER CORRECTION
462	.Audio		(E.G., DYNAMIC REPRODUCTION)
463	.Full field	498	.Specified color
464	.Sync	499	Using frequency shifting (e.g.,
465	.Data separation or detection		heterodyne)
466	Error correction or prevention	500	SYNCHRONIZATION
467	-	501	
	.Data format		Reprocessing
468	.Including teletext decoder or	502	Specified color
	display	503	.For sequential color components
469	FORMAT	504	With line rate switch (e.g.,
470	.Adapted to reduce noise or for		SECAM)
	frequency modulation (e.g.,	505	.Phase locking regenerated
	variable gain)		subcarrier to color burst
471	.Including pulse modulation of	506	Burst gate
	video signal (e.g., pulse	507	Including demodulator
	width, PAM)	508	Digital
472	Pulse code modulation	509	
473	ruise code modulation .Including additional information	509	With line rate switch (e.g.,
_			PAL)
474	For controlling video	510	.Locking of computer to video
	processing (e.g., digitally		timebase
	assisted video)	511	.Control of picture position
475	Additional modulation of	512	.Locking of video or audio to
	picture carrier (e.g.,		reference timebase
	quadrature)	513	Frame or field synchronizers
476	During sync, blanking, or	514	Color television
	overscan	515	Audio to video
477	During both vertical and		
1//	horizontal blanking	516	By controlling video or sync
478	_		generator
	During vertical blanking	517	Color television
479	During horizontal blanking	518	Including compensation for
480	Sound signal		transmission delays
481	Plural (e.g., stereo or SAP)	519	Color television
482	Sound signal	520	Color
483	Plural (e.g., stereo or SAP)	521	.Sync generation
484	Sound signal	522	Means on video signal generator
485	Plural (e.g., stereo or SAP)		
486	Including the use of a	523	With addressable memory
TUU	subcarrier	524	With counter or frequency
	puncatitet		divider

525	.Sync separation	563	.For display of additional
526	Field or frame identification		information
527	Color	564	Simultaneously and on same
528	Including automatic gain		screen (e.g., multiscreen)
	control (AGC)	565	Picture in picture
529	To produce distinct vertical	566	Color television
	output	567	Memory
530	With distinct horizontal	568	Compression
	output	569	Receiver indicator (e.g., on
531	To produce distinct horizontal		screen display)
	output	570	Tuning indication
532	By amplitude	571	IMAGE SIGNAL PROCESSING CIRCUITRY
533	Noise reduction		SPECIFIC TO TELEVISION
534	Amplitude limiting	572	.A/D converters
535	Noise inversion	573	Analog to binary
536	.Automatic phase or frequency	574	Including dither
	control	575	.Video reprocessing
537	Of sampling or clock	576	.Selective image modification
538	With data interpolation		(e.g., touch up)
539	Color	577	Color change type
540	Horizontal sync component	578	.Special effects
541	Cascaded phase or frequency	579	Strobe (e.g., ball tracker)
311	adjusting	580	Geometric transformation
542	Plural distinct operating	581	Size change
312	modes	582	Color signal
543	Line rates	583	Rotation
544	Locking rates	584	Combining plural sources
545	Different mode during	585	
343	vertical blanking		Including priority key
546	Countdown	586	Foreground/background insertion
547		F 0 7	
548	Vertical sync componentCountdown	587	Including hue detection
549		E00	(e.g., chroma key)
	Using color subcarrier	588	Multiple distinct images
550	.To achieve interlaced scanning	F00	(e.g., splitscreen)
551	.Of mechanical scan	589	Including insertion of
552	COMBINED WITH DIVERSE ART DEVICE		characters or graphics (e.g.,
FF2	(E.G., COMPUTER, TELEPHONE)	590	titles)
553	BASIC RECEIVER WITH ADDITIONAL	590	Specified details of key
 4	FUNCTION		signal generation or
554	.Multimode (e.g., composite, Y,	591	processing
	C; baseband RF)	39I	Self keyers (e.g., key
555	For receiving more than one		generated from video being mixed
	format at will (e.g., NTSC/	592	
F.F.C	PAL)	594	Chroma key (e.g., hue detector)
556	For format with different	593	
	aspect ratio		Artificial key generation
557	Color processing	594	Wipes signal generator
558	Format detection	595	Fades signal generator
559	.Instant replay or freeze frame	596	Window signal generator
560	Color television processing		(e.g., rectangle)
561	.For magnification of part of	597	For generation of soft edge
	image		(e.g., blending)
562	Color television	598	Specified details of signal
			combining
		599	Color signal

002 Display controlled by ambient 1 light	600	Graphic or character insertion type	629	Including horizontal transition
Display controlled by ambient light Light Chrominance transition controls Sound muting Saturation and contrast G32 Sound muting Chrominance transition Control	601	Marker or pointer generator	630	Color television processing
saturation and contrast control) 634 .Including picture blanking control) 634 .Picture blanking detection controlling 636 .At transmitter processing 637 .Retrace type 637 .Retrace type 638 .Chrominance signal demodulator reference (e.g., VIR) 639 .Digital .Por quadrature signal (e.g., NSC) reduction and transition sharpening 641 .Por quadrature signal (e.g., NSC) .Processing at encoder or transmitter (e.g., precord correction) 642 .Color encoder or chrominance luminance cross-talk (e.g., precord) control (e.g., saturation) 649 .Reduction of chrominance luminance cross-talk (e.g., precord) control (e.g., saturation) 640 .At transmitter (e.g., precord) 641 .Thelluding chrominance signal amplitude control (e.g., saturation) 642 .Color killer .Thelluding control (e.g., saturation) 643 .Chrominance signal amplitude control (e.g., saturation) 644 .Automatic .Picture responsive (e.g., precomphasis - deemphasis) 648 .Picture responsive (e.g., overload) precomplasis - deemphasis) 649 .Picture responsive (e.g., overload) precomplasis - deemphasis of 647 .Automatic .Picture responsive (e.g., overload) for subcarrier fixed pattern defects) 651 .Blackspot or shading correction (e.g., corrects for fixed pattern defects) 652 .Scene by scene color correction (e.g., corrects for fixed pattern defects) 653 .Sephase change of chrominance signal or subcarrier .Spy phase change of chrominance signal or subcarrier .Color balance or temperature (e.g., white balance) .Including potical sensor to observe display (e.g., CRT) .Making (e.g., R, G, B to R', G', B') .Chrominance phase adjuster (e.g., inverter) .Chrominance phase adjuster (e.g., inverter) .Chrominance signal amplitude pattern defects .Chrominance signal amplitude responsive peaking ontrol .DigitalPicture responsive (e.g., or .Picture responsive (e.g., or .Picture responsive (e.g., resplacement type)Picture responsive (e.g., resplacement signal or subcarrierPicture responsive (e.g., resplacement signal or subcarrierPicture responsive (e.g., resplacemen	602	.Display controlled by ambient		Luminance transition controls
control) Including nonstandard signal detection controlling processing (37 processing (38 processing (38 processing (38 processing (38 processing (38 processing (39 proce	603	Specified color (e.g.,	632	.Sound muting
control) Including nonstandard signal detection controlling processing processing and election controlling processing and election controlling processing and election does reduction and transition sharpening and transition sharpening are reduction as a correction are reduction as a correction are reduction as a correction are reduction of chrominance luminance cross-talk (e.g., precomb) 100		saturation and contrast	633	Including picture blanking
Including nonstandard signal detection controlling processing G36		control)	634	
detection controlling processing and processing and processing and processing and combined noise reduction and transition sharpening are reference (e.g., VIR) and transition sharpening are reduction and transition sharpening are duction of color transmitter (e.g., pre- data are duction of chrominance are demonstrated as a signal modulator and transition for the data are demonstrated as a signal modulator and transition and transition are demonstrated as a signal modulator and transition and transition are demonstrated as a signal modulator and transition and transition are demonstrated as a signal modulator and transition and transition are demonstrated as a signal modulator and transition and transition are demonstrated as a signal modulator and transition and transition and transition and transition and transition and transition signal amplitude control (e.g., saturation) and transition and transition and transition and transition are demonstrated as a signal modulator and amplitude control (e.g., saturation) and transition and transit	604	.Including nonstandard signal	635	_
processing Including vertical interval reference (e.g., VIR) Combined noise reduction and transition sharpening transition sharpening Or Noise or undesired signal reduction Or Processing at encoder or transmitter (e.g., precorrection) Or Reduction of chrominance luminance cross-talk (e.g., precorrection) Or Reduction of chrominance luminance cross-talk (e.g., precorrection) Or Reduction of chrominance luminance signal amplitude control Or Reduction of chrominance luminance ross-talk (e.g., precorrection) Or Reduction of chrominance signal modulator Or NTSC) Or Reduction of chrominance signal modulator Or Reduction of chrominance signal modulato			636	.At transmitter
Including vertical interval reference (e.g., VIR) 638 Chrominance signal demodulator reference (e.g., VIR) 639 Digital				
reference (e.g., VIR) 639Digital Combined noise reduction and 640PAL signal transition sharpening 641For quadrature signal (e.g., norection) 608Processing at encoder or transmitter (e.g., precorection) 609Reduction of chrominance luminance cross-talk (e.g., precorection) 610Adaptive 646Digital 611To suppress echo 647Automatic 612Color signals 648Picture responsive (e.g., precomb) 649Reduction (e.g., saturation) 613Complementary system (e.g., precomb) 649Learned for precemb) 640Digital 614Complementary system (e.g., precomb) 640Digital 615Blackspot or shading correction (e.g., corrects for fixed pattern defects) 616Pror color television 640Dropout compensator (e.g., replacement type) 651For removal of low amplitude random noise (e.g., variable bandwidth) 652Por retored of the delays (e.g., motion adaptive) 653Dropout compensator (e.g., motion adaptive) 654Por color television 655Including feedback controlIncluding optical sensor to observe display (e.g., CRT)Matrixing or mixingDigitalIncluding optical sensor to observe display (e.g., CRT)Matrixing or mixingDigitalMatrixing or mixingLearnedLe	605			
Combined noise reduction and transition sharpening (a)				
transition sharpening 61	606			_
Noise or undesired signal reduction 642 Color encoder or chrominance signal modulator Color killer Color encoder or chrominance Color killer C				_
reduction 642 .Color encoder or chrominance signal modulator transmitter (e.g., precorrection) 644 .Including chrominance signal modulator transmitter (e.g., precorrection) 644 .Including chrominance signal amplitude control luminance cross-talk (e.g., precomb) 645 .Chrominance signal amplitude control (e.g., saturation) 646 .Digital 610Adaptive 646 .Digital 611To suppress echo 647 .Automatic 612Color signals 648Picture responsive (e.g., preemphasis - deemphasis) 649 .Hue control (e.g., preemphasis - deemphasis) 649 .Hue control 611Digital 612Complementary system (e.g., preemphasis - deemphasis) 651Digital 613Digital 614Digital 615Digital 615Digital 616Digital 616Digital 617Picr color television 618For color television 619Picr color television 610Picr color television 611Digital 612Picr color television 613Digital 614Picr color television 615Digital 616Picr color television 616Picr color television 617Picr color television 618Picr removal of low amplitude 619Picr color television 619Picr color television 610Picr col	607		041	
Signal modulator Signal mamplitude Control (e.g., saturation) Signal mamplitude Signal modulator Signal mamplitude Signal	007	_	640	•
transmitter (e.g., precorrection) 3. Reduction of chrominance luminance cross-talk (e.g., precomb) 1. Reduction of chrominance luminance cross-talk (e.g., precomb) 3. Reduction of chrominance luminance cross-talk (e.g., precomb) 4. Landaptive 6. Landaptive	608		642	
correction) 1. Reduction of chrominance luminance cross-talk (e.g., precomb) 1. Laminance cross-talk (e.g., precombon) 1. Laminan	000		- 40	3
Composition of chrominance luminance cross-talk (e.g., precomb) Chrominance signal amplitude control (e.g., saturation)				
luminance cross-talk (e.g., precomb) Chrominance signal amplitude control (e.g., saturation) 10	600	,	644	
control (e.g., saturation) 10	009			
610Adaptive 611To suppress echo 612Color signals 613Complementary system (e.g., preemphasis - deemphasis) 614Ghost elimination (e.g., multipath) 615Blackspot or shading correction (e.g., corrects for fixed pattern defects) 616Dropout compensator (e.g., replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 621For color television 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 621Coring type 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 621For color television 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 620Coring type 621For color television 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 620Coring type 621For color television 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 620Coring type 620Coring type 621Toriluding processing to prevent 622Coring type 623Coring type 624For color television 625Coring type 626Coring type 627Coring type 628Coring type 629Coring type 629Coring type 620		precomb)	645	
612Color signals 613Complementary system (e.g., preemphasis - deemphasis) 614Ghost elimination (e.g., multipath) 615Blackspot or shading correction (e.g., corrects for fixed pattern defects) 616Dropout compensator (e.g., replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625Tansition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 649Complementary system (e.g., some color to correction overload) 650Scene by scene color correction 651Bute control 652Fleshtone corrector (e.g., fixed) 653By phase change of chrominance signal or subcarrier 654By phase change of chrominance signal or subcarrier 655Color balance or temperature (e.g., white balance) 656Enceiver type 657Including feedback control 658Including optical sensor to observe display (e.g., CRT) 659Matrixing or mixing 660Digital 661Masking (e.g., R, G, B to R', G', B') 662Corninance phase adjuster 663Chrominance-luminance signal separation 664Chrominance-luminance signal separation 665Including comb filter (e.g., using line, field, frame delays)	610	Adaptive	646	
complementary system (e.g., preemphasis - deemphasis) 649	611		647	Automatic
overload) preemphasis - deemphasis) 649	612	Color signals	648	Picture responsive (e.g.,
preemphasis - deemphasis) 614Ghost elimination (e.g., multipath) 615Blackspot or shading correction (e.g., corrects for fixed pattern defects) 616Dropout compensator (e.g., replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., corrects) for edge with the edge with th	613	Complementary system (e.g.,		
614Ghost elimination (e.g., multipath) 615Blackspot or shading correction (e.g., corrects for fixed pattern defects) 616Dropout compensator (e.g., replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 63Scene by scene color correctionDigital Digital Digital Fleshtone corrector (e.g., fixed) By phase change of chrominance signal or subcarrier By phase change of chrominance signal		preemphasis - deemphasis)	649	•
multipath) 615Blackspot or shading correction	614	Ghost elimination (e.g.,		
615		multipath)		
(e.g., corrects for fixed pattern defects) 616 Dropout compensator (e.g., replacement type) 617 Defor television 618 For removal of low amplitude random noise (e.g., variable bandwidth) 619 Deformed frame or field delays (e.g., motion adaptive) 620 Deformed frame or field delays (e.g., motion adaptive) 621 Deformed frame or field delays (e.g., motion adaptive) 622 Deformed frame or field delays (e.g., motion adaptive) 623 Deformed frame or field delays (field frame) 624 Deformed frame or field delays (field frame) 625 Deformed frame or field delays (field frame) 626 Deformed frame or field delays (field frame) 627 Deformed frame or field delays (field frame) 628 Deformed frame or field delays (field frame) 629 Deformed frame or field delays (field frame) 620 Deformed frame frame frame frame frame frame (field frame) 620 Deformed frame frame frame frame frame frame (field frame) 621 Deformed frame frame frame frame frame (field frame) 622 Deformed frame frame frame frame frame (field frame) 623 Deformed frame frame frame frame frame (field frame) 624 Deformed frame frame frame frame frame (field frame) 625 Deformed frame	615	Blackspot or shading correction		
616Dropout compensator (e.g., replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 638By phase change of chrominance signal signal or subcarrier 640By phase change of chrominance signal or subcarrier 654By phase change of chrominance signal or subcarrier 655By phase change of chrominance signal or subcarrier 656By phase change of chrominance signal or subcarrier 658By phase change of chrominance signal or subcarrier 659By phase change of chrominance signal or subcarrier 665By phase change of chrominance signal or subcarrier 665Color balance or temperature (e.g., white balance) 666Including feedback control 667Including optical sensor to observe display (e.g., CRT) 668Including optical sensor to observe display (e.g., CRT) 669Including optical sensor to observe display (e.g., R, G, B to R', G', B') 670Including optical sensor to observe display (e.g., CRT) 680Including optical sensor to observe display (e.g., R, G, B to R', G', B') 681Including optical sensor to observe display (e.g., R, G, B to R', G', B') 68				fixed)
replacement type) 617For color television 618For removal of low amplitude random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 658By phase change of chrominance signal or subcarrier .By phase change of chrominance signal or subcarrier .Color balance or temperature (e.g., white balance) Including pedback control Including optical sensor to observe display (e.g., CRT) Matrixing or mixingDigitalMasking (e.g., R, G, B to R`, G`, B`) Chrominance phase adjuster (e.g., inverter) Including comb filter (e.g., including comb filter (e.g., using line, field, frame delays)	616		653	
617For color television 618For removal of low amplitude	0_0			
Signal or subcarrier Color balance or temperature (e.g., white balance) Endowmoniate (e.g., variable bandwidth) 619 Averaging type 620 Using frame or field delays (e.g., motion adaptive) 621 For color television 622 Noise component generator, limiter, subtractor type 623 Coring type 624 For color television 625 Transition or edge sharpeners 626 Scanning velocity modulation 627 Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) Signal or subcarrier (e.g., white balance) Receiver type (e.g., white balance) Receiver typeIncluding feedback control Including optical sensor to observe display (e.g., CRT) Matrixing or mixingDigitalMasking (e.g., R, G, B to R', G', B') Chrominance phase adjuster (e.g., inverter) Chrominance-luminance signal separation Logic circuit typeIncluding comb filter (e.g., using line, field, frame delays)	617		654	
random noise (e.g., variable bandwidth) 619Averaging type 620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 658Receiver type 657Including feedback control 658Including optical sensor to observe display (e.g., CRT) 660DigitalMasking (e.g., R, G, B to R', G', B') 661Masking (e.g., R, G, B to R', G', B') 662Chrominance phase adjuster (e.g., inverter) 663Coring analyse comb filter (e.g., using line, field, frame delays)				3
bandwidth) 619Averaging type 620Using frame or field delays	010		655	
1. Averaging type 2Averaging type 3Averaging type 3Including feedback control 3Including optical sensor to observe display (e.g., CRT) 3Noise component generator, limiter, subtractor type 3Coring type 3Coring type 3For color television 3Coring type 3Coring type 3Coring type 3Coring type 4For color television 5Coring type 5Coring type 6Including optical sensor to observe display (e.g., CRT) 6Digital 6Masking (e.g., R, G, B to R`, G`, B`) 6Chrominance phase adjuster 6Chrominance phase adjuster 6Chrominance-luminance signal 6Including comb filter (e.g., using line, field, frame delays) 6Including feedback control 6Including optical sensor to observe display (e.g., CRT) 6Including optical sensor to observe display (e.g., CRT) 6Including or mixing 6Digital 6Masking (e.g., R, G, B to R`, 6Chrominance phase adjuster 6Including comb filter (e.g., using line, field, frame delays)				_
620Using frame or field delays (e.g., motion adaptive) 621For color television 622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including feedback control 658Including optical sensor to observe display (e.g., CRT) 659Matrixing or mixing 660Digital 661Masking (e.g., R, G, B to R`, G`, B`) 662Chrominance phase adjuster (e.g., inverter) 663Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 664Including comb filter (e.g., using line, field, frame delays)	610		656	
(e.g., motion adaptive) (e.g., motion adaptive) (e.g., motion adaptive) (observe display (e.g., CRT) (observe display (e.g		5 5 11	657	Including feedback control
621For color television 622Noise component generator,	020		658	Including optical sensor to
622Noise component generator, limiter, subtractor type 623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 659 .Matrixing or mixing 660DigitalMasking (e.g., R, G, B to R', G', B') 662 .Chrominance phase adjuster (e.g., inverter) 663 .Chrominance-luminance signal separationLogic circuit typeIncluding comb filter (e.g., using line, field, frame	C 0 1			observe display (e.g., CRT)
limiter, subtractor type 623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent 628 the addition of noise (e.g., 629 coring enhancement signal, 70 noise responsive peaking 630 chrominance phase adjuster (e.g., inverter) 640 chrominance-luminance signal 651 separation 652 chrominance signal 663 chrominance-luminance signal 664 choice separation 665 chrominance-luminance signal 665 chrominance-luminance signal 666 chrominance-luminance signal 667 chrominance-luminance signal 668 chrominance-luminance signal 669 chrominance-luminance signal 660 chrominance phase adjuster 660 chrominance phase adjuster 660 chrominance phase adjuster 660 chrominance phase adjuster 661 chrominance phase adjuster 662 chrominance-luminance signal 663 chrominance-luminance signal 664 chrominance-luminance signal 665 chrominance-luminance signal 666 chrominance-luminance signal 667 chrominance-luminance signal 668 chrominance-luminance signal 669 chrominance-luminance signal 669 chrominance-luminance signal 660 chrominance-luminance signal 660 chrominance-luminance signal 661 chrominance-luminance signal 662 chrominance-luminance signal 663 chrominance-luminance signal 664 chrominance-luminance signal 665 chrominance-luminance signal 666 chrominance-luminance signal 667 chrominance-luminance signal 668 chrominance-luminance signal 669 chrominance-luminance signal 669 chrominance-luminance signal 660 chrominance-luminance signal 661 chrominance-luminance signal 662 chrominance-luminance signal 663 chrominance-luminance signal 664 chrominance-luminance signal 665 chrominance-luminance signal 667 chrominance-luminance signal 668 chrominance-luminance signal 669 chrominance-luminance signal 660 chrominance-luminance signal 660 chrominance-luminance signal			659	.Matrixing or mixing
623Coring type 624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent 628 the addition of noise (e.g., 629 coring enhancement signal, 700 noise responsive peaking 630 chrominance phase adjuster (e.g., inverter) 640Logic circuit type 651Masking (e.g., R, G, B to R, 67	622		660	Digital
624For color television 625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent 628 the addition of noise (e.g., 629 coring enhancement signal, 700 noise responsive peaking 630 chrominance phase adjuster (e.g., inverter) 640 chrominance-luminance signal 650 separation 661 chrominance phase adjuster (e.g., inverter) 662 chrominance phase adjuster 663 chrominance phase adjuster (e.g., inverter) 663 chrominance phase adjuster 664 chrominance phase adjuster 665 chrominance phase adjuster 666 chrominance phase adjuster 667 chrominance phase adjuster 668 chrominance phase adjuster 669 chrominance phase adjuster 660 chrominance phase adjuster 661 chrominance phase adjuster 662 chrominance phase adjuster 663 chrominance phase adjuster 664 chrominance phase adjuster 665 chrominance phase adjuster 666 chrominance phase adjuster 667 chrominance phase adjuster 668 chrominance phase adjuster 669 chrominance phase adjuster 660 chrominance phase adjuster 660 chrominance phase adjuster 661 chrominance phase adjuster 662 chrominance phase adjuster 663 chrominance phase adjuster 664 chrominance phase adjuster 665 chrominance phase adjuster 666 chrominance phase adjuster 667 chrominance phase adjuster 668 chrominance phase adjuster 669 chrominance phase adjuster 669 chrominance phase adjuster 669 chrominance phase adjuster 660 chrominance phase adjuster 661 chrominance phase adjuster 662 chrominance phase adjuster 663 chrominance phase adjuster 664 chrominance phase adjuster 665 chrominance phase adjuster 666 chrominance phase adjuster 667 chrominance phase adjuster 668 chrominance phase adjuster 669 chrominance phase adjuster 669 chrominance phase adjuster 660 chrominance phase adjuster 660 chrominance phase adjuster 661 chrominance phase adjuster 662 chrominance phase adjuster 663 chrominance phase adjuster 664 chrominance phase adjuster 665 chrominance phase adjuster 666 chrominance phase adjuster 667 chrominance phase adjuster 668 chrominance phase adjuster 669 chrominanc	600		661	Masking (e.g., R, G, B to R`,
625 .Transition or edge sharpeners 626Scanning velocity modulation 627Including processing to prevent 628 the addition of noise (e.g., 629 coring enhancement signal, 629 noise responsive peaking 630 chrominance phase adjuster (e.g., inverter) 640Chrominance phase adjuster (e.g., inverter) 650Chrominance phase adjuster (e.g., inverter) 661Logic circuit type 662Including comb filter (e.g., 663 using line, field, frame 663 chrominance phase adjuster (e.g., inverter) 664 separation 665Including comb filter (e.g., 665 using line, field, frame				G`, B`)
1. Transition or edge sharpeners 2. Scanning velocity modulation 3. Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 2. Transition or edge sharpeners (e.g., inverter) 3. Chrominance-luminance signal separation 4. Logic circuit type 5. Including comb filter (e.g., using line, field, frame delays)			662	.Chrominance phase adjuster
626Scanning velocity modulation 627Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 663Chrominance-luminance signal separationLogic circuit typeIncluding comb filter (e.g., using line, field, frame				
1. Including processing to prevent the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 1. Including processing to prevent separation the addition of noise (e.g., 664 coring enhancement signal, 665 coring enhan			663	
the addition of noise (e.g., coring enhancement signal, noise responsive peaking control) 664Logic circuit type 665Including comb filter (e.g., using line, field, frame	627	3 1 3 1		
coring enhancement signal, noise responsive peaking control) 665Including comb filter (e.g., using line, field, frame		_	664	-
noise responsive peaking using line, field, frame control)				
control)			000	
628Vertical transition				
	628	Vertical transition		

666	Including adaptive artifacts removal (e.g., switchable trap	700	.Motion dependent key signal generation or scene change
	or LPF in luma channel)		detection
667	Adaptive comb filter	701	Specified processing of frame
668	Selects or blends two or more		or field difference signal
	separated signals to derive output		<pre>(e.g., noise reduction, key signal spreading)</pre>
669	Including frame or field	702	Composite color signal
	delays (e.g., motion adaptive)	703	.Hue or saturation detector
670	Including frame or field	704	.Sweep expansion or reduction
	delays	705	.Switching
671	.Gray scale transformation	706	receiver type
672	Using histogram	707	.Amplifiers
673	Combined contrast control and	708	.Color television signal
	brightness or DC level control		processing
674	Nonlinear amplitude	709	Signal modification for one gun
	modification (e.g., gamma)		color tube (e.g., dot
675	Color television		sequential)
676	By adding outputs from	710	Differential phase or amplitude
	parallel channels		responsive
677	With specified DC level	711	Frequency response modification
•	control	712	Luminance channel circuitry
678	Automatic range control (e.g.,	713	Chrominance channel circuitry
070	AGC, automatic contrast	714	.With details of static storage
	control)	,	device
679	Color television	715	For storing a sequence of
680	At transmitter	713	frames or fields
681	Carrier envelope	716	Specified data formatting
682	Sync or blanking	, 10	(e.g., memory mapping)
683	Noise reduction or	717	Of color signal
003	elimination	718	Accessing circuitry
684	Keyed	719	Including processor interface
685	Delayed AGC	, 10	(e.g., CPU)
686	Manual contrast control (e.g.,	720	.Digital
000	linear)	721	Plural processing units
687	.Brightness control	722	STUDIO EQUIPMENT
688	By subtracting averaged active	723	TELEVISION TRANSMITTER CIRCUITRY
000	video portion (e.g., flare)	723	.Modulator
689	With DC clamping	725	RECEIVER CIRCUITRY
690	.White limiter	726	.Demodulator
691	.DC insertion	727	Color television
692	Color television	727	.Color television
693	At transmitter	729	.Television receiver adapted to
694		129	receive radio broadcast or in
	For plural signals or signal components		combination with radio
695	Level inserted during keying		receiver
	signals (e.g., keyed clamp)	730	.Power supply
696	Insertion level derived by key	731	.Tuning
	signals	732	Search tuning
697	Level derived within feedback	733	Tuning voltage
	path	734	.Remote control
698	Diode	735	.Automatic frequency control
699	.Motion vector generation	736	.Sound traps
		737	.Intercarrier circuits
		738	.Sound circuit

739	VIDEO DISPLAY	777	With intensifier
740	.Array of shutters	778	Plural CRTs
741	.Red-white phenomena	779	With optical element
741		780	Beam combining
742	.Color sequential	781	_
_	With moving color filters	_	With optical element
744	.Projection device	782	Mirror arrangement
745	With alignment, registration or	783	Concave mirror
5 46	focus	784	With correcting plate
746	Raster shape distortion	785	Adjustable
747	Raster size or position compensation	786	With screen or absorption filter
748	With cooling device	787	Cabinet or chassis
749	Liquid	788	Folding
750	Plural parallel light	789	Cabinet or chassis
	modulators	790	.Liquid crystal
751	Liquid crystal	791	Color TV
752	Using birefringent or	792	Scanning circuit
	polarizing medium (e.g., Kerr	793	Interlacing
	cell, Pockel`s cell, etc.)	794	With cabinet or housing
753	Electron beam addressed	,,,,	structure
754	Acousto-optic (e.g., Bragg	795	.Direct viewed light valve
	cell, etc.)	796	.Vacuum panel
755	Deformable medium	797	.Gas discharge
756	With optical element	798	.Array of lamps
757	Beam combining	799	Color TV
758	Plural serial light modulators	800	
759	Single light modulator	800	.Electroluminescent (e.g.,
760	Color TV	0.01	scanned matrix, etc.)
761		801	Light emitting diode
761	Liquid crystal	802	Color TV
702	Using birefringent or	803	Color TV
	polarizing medium (e.g., Kerr	804	.With optical fiber device
762	cell, Pockel`s cell, etc.)	805	.Cathode-ray tube
763	Electron beam addressed	806	With distortion, alignment or
764	Deformable medium		focus
765	Fluid	807	Color convergence correction
766	Liquid crystal	808	Color TV
767	Using birefringent or	809	Separate electron beams in
	polarizing medium (e.g., Kerr		single tube
	cell, Pockel`s cell, etc.)	810	One electron beam supplying
768	Electron beam addressed		more than one color
769	Acousto-optic	811	Beam position indicating
770	Deformable medium	812	Horizontal stripes
771	Including solid-state	813	Photoelectric sensor
	deflection elements (e.g.,	814	Secondary emission sensor
	deformable mirror device	815	With electron-optical color
	(DMD))		selection
772	Medium in tape, ribbon, or	816	With color specific optical
	membrane form		device
773	Fluid medium	817	Electrochromic device
774	Deformed into diffraction	818	Protective device
	grating (e.g., using electron	819	Radiation protection for user
	beam)	820	External electric or magnetic
775	Having significant chemical		effect
	composition	821	Implosion protection
776	Cathode-ray tube image source	- -	

CLASS 348 TELEVISION 348 - 13

822	Tensioned band	
823	Protective glass or panel	
824	Bonded to CRT faceplate	
825	Support	FOREIGN ART COLLECTIONS
826	CRT having only support at	
	front portion	FOR 000 CLASS-RELATED FOREIGN DOCUMENTS
827	CRT position adjustable by	
	user	Any foreign patents or non-patent litera-
828	Deflection element support	ture from subclasses that have been
829	Yoke	reclassified have been transferred
830	Supported by CRT neck	directly to FOR Collections listed below.
831	Adjustable	These Collections contain ONLY foreign
832	With optical element	patents or non-patent literature. The par-
833	For line elimination	enthetical references in the Collection
834	Glare reduction	titles refer to the abolished subclasses from which these Collections were derived.
835	Filters	from which these collections were derived.
836	.Cabinet or chassis	
837	With vehicle	
838	Portable	
839	Modular	FOR 100 BANDWIDTH REDUCTION SYSTEM (348/
840	Multiple screens	384)
841	Masking	FOR 101 .Plural video programs in single
842	Light shielding	channel (348/385)
843	Cabinet back	FOR 102Color television (348/386)
844	MISCELLANEOUS	FOR 103Bit-rate reduction (348/387)
		FOR 104 .Multiple channel (e.g., plural carrier) (348/388)
		FOR 105 Including one conventional or
CROSS-I	REFERENCE ART COLLECTIONS	compatible channel (e.g., two channel NTSC systems) (348/389)
901	HIGH SPEED TELEVISION SYSTEM	FOR 106 .Bit-rate reduction (348/390)
902	PHOTOCHROMIC	FOR 107 Specified color signal (348/
903	INCLUDING SIDE PANEL INFORMATION	391)
	IN SINGLE CHANNEL	FOR 108 Sub-Nyquist sampling (348/392)
904	SEPARATION OR JOINING OF SIDE AND	FOR 109Direct coding of color
	CENTER PANELS	composite signal (348/393)
905	REPRODUCTION OF A COLOR FIELD OR	FOR 110 Predictive coding (348/394)
	FRAME	FOR 111Transform coding (348/395)
908	CONVERTIBLE CIRCUITS (E.G., Y/C	FOR 112Including luminance signal
000	SEPARATION OR NOISE REDUCTION)	(348/396)
909	NOISE RESPONSIVE SIGNAL	FOR 113 Using separate coders for
010	PROCESSING	different picture features
910	FLICKER REDUCTION	(e.g., highs, lows) (348/397)
911	LINE DOUBLER ADAPTED FOR	FOR 114 Sub-band encoding (e.g., low
	REPRODUCING PROGRAM ORIGINALLY FROM FILM (E.G., 24 FRAME PER	horizontal/low vertical
	SECOND)	frequency, low horizontal/high
912	DIFFERENTIAL AMPLITUDE	vertical frequency) (348/398)
714	CONSIDERATION (E.G., AMPLITUDE	FOR 115Picture feature dependent
	VS. FREQUENCY)	sampling rate or sample
913	LETTERBOX (E.G., DISPLAY 16:9	selection (348/399)
	ASPECT RATIO IMAGE ON 4:3	FOR 116 Involving hybrid transform and
	SCREEN)	difference coding (348/400)
	-	FOR 117With prior difference coding
914	DELAY FOR EQUALIZATION	(348/401)

- FOR 118Including motion vector (348/402)
- FOR 119 ..Involving transform coding (348/403)
- FOR 120 ... Adaptive (348/404)
- FOR 121Quantizer (348/405)
- FOR 122Normalizer (348/406)
- FOR 123Motion (348/407)
- FOR 124 ...Transformed sample selection (e.g., hierarchical sample selection) (348/408)
- FOR 125 .. Involving difference transmission (348/409)
- FOR 126 ...Involving both PCM and DPCM encoding (348/410)
- FOR 127 ...Plural predictors (348/411)
- FOR 129Including motion vector (348/413)
- FOR 130Involving vector quantization (348/414)
- FOR 131 ...Including temporal prediction (e.g., frame difference) (348/415)
- FOR 132Including motion vector (348/416)
- FOR 133Involving vector quantization (348/417)
- FOR 134 ...Involving vector quantization (348/418)
- FOR 135 ...Coding element controlled by buffer fullness (e.g., adaptive quantizer) (348/419)
- FOR 136 .. Involving block coding (348/420)
- FOR 137 ...PCM represents minimum, maximum, or average of block (348/421)
- FOR 138 .. Involving vector quantization (348/422)
- FOR 139 ..Arrangements for multiplexing one video signal, one or more audio signals, and a synchronizing signal (348/423)
- FOR 140 .. Sub-Nyquist sampling (348/424)
- FOR 141 ... Adaptive (348/425)
- FOR 142 ..Associated signal processing (348/845)
- FOR 143 ...Involving error detection or correction (348/845.1)
- FOR 144 ...Involving signal formatting (348/845.2)

- FOR 145 ...Involving synchronization (348/845.3)
- FOR 146 .Format type (e.g., HDTV or EDTV) (348/426)
- FOR 147 .. Including frequency folding (e.g., subsampling) (348/427)
- FOR 148 ...Spotwobble (e.g., pixels from plural lines form single transmitted line) (348/428)
- FOR 149 ...Including video related information (e.g., digitally assisted television) (348/429)
- FOR 150 ... Using two or more frames (348/ 430)
- FOR 151Motion adaptive (348/431)
- FOR 152 ..Added video information in standard channel format (e.g., compatible EDTV) (348/432)
- FOR 153 ...Including additional modulation of picture carrier (e.g., quadrature) (348/433)
- FOR 154 ...Including information in sync, blanking, or overscan (348/434)
- FOR 155During vertical blanking interval (348/435)
- FOR 156 ...Including the use of a subcarrier (348/436)
- FOR 157 ..Individual processing of different parts of image frequency band (e.g., sum and difference, high band/low band) (348/437)
- FOR 158 .Individual processing of different parts of image frequency band (e.g., sum and difference, high band/low band) (438/438)
- FOR 159 .Frame field or line dropping followed by time expansion and time compression (348/439)
- FOR 160 .Scan rate variation (348/440)

 CAMERA, SYSTEM AND DETAIL (348/
 207)
- FOR 161 .With electronic viewfinder or display monitor (348/333)
- FOR 162 .. With indicium (348/334)
- FOR 163 USE SURVEY AND ACCOUNTING (348/1)
- FOR 164 .Monitoring of physical reaction of viewer (348/2)
- FOR 165 .With billing (348/3)
- FOR 166 .Monitoring of synchronization or blanking pulse (e.g., horizontal or vertical pulse signal) (348/4)

CLASS 348 TELEVISION 348 - 15

- FOR 167 .With video cassette recorder (VCR) (348/5)
- FOR 168 USE OR ACCESS BLOCKING (E.G., LOCKING SWITCH) (348/5.5)
- FOR 169 WIRED BROADCAST (E.G., CABLE) (348/6)
- FOR 170 .Broadcast on demand (348/7)
- FOR 172 .Controlled signal substitution (e.g., emergency warning, local preemption, etc.) (348/9)
- FOR 173 .With subscriber terminal details (348/10)
- FOR 174 .. For frequency conversion (348/ 11)
- FOR 175 .Two-way (348/12)
- FOR 176 TWO-WAY (E.G., INTERACTIVE) (348/
- FOR 177 .With voice capability (e.g., videophone) (348/14)
- FOR 178 ...Conferencing (348/15)
- FOR 179 ... Switching (348/16)
- FOR 180 .. Transmission scheme (348/17)
- FOR 181 ...Still frame (i.e., freeze frame) (348/18)
- FOR 182 ...Field or frame difference (e.g., moving frame) (348/19)
- FOR 183 .. User positioning (e.g., parallax) (348/20)
- FOR 184 CAMERA, SYSTEM AND DETAIL (348/ 207)
- FOR 185 .Camera image stabilization (348/ 208)
- FOR 186 .With flying spot scanner (348/ 209)
- FOR 187 ... For color scanning (348/210)
- FOR 188 .Remote control (348/211)
- FOR 189 ..By multiplexed control signals (e.g., duplexing, etc.) (348/212)
- FOR 190 ..Preprogrammed or stored control instructions (348/213)
- FOR 191 ..Body movement actuation (348/ 214)
- FOR 192 .With streak device (348/215)
- FOR 193 .Low light level (348/216)
- FOR 194 ..With image intensifier (348/ 217)
- FOR 195 .Unitary image formed by compiling sub-areas of same scene (e.g., array of cameras) (348/218)

- FOR 196 .Swing driven
- FOR 197 .Still and motion modes of operation (348/220)
- FOR 198 .. Exposure control (348/221)
- FOR 199 .Combined image signal generator and general image signal processing (348/222)
- FOR 200 ..Color balance (e.g., white balance) (348/223)
- FOR 202 ...With means for preventing colored object from effecting color balance (348/225)
- FOR 203 ...Including flicker detection (e.g., fluorescent (348/226)
- FOR 204 ...With ambient light sensor (348/227)
- FOR 205 ...Responsive to output signal (348/228)
- FOR 206 ..Combined automatic gain control and exposure control (i.e., sensitivity control (348/229)
- FOR 207 ...Readout of solid-state image sensor considered or altered (348/230)
- FOR 208 ..With details of static memory for output image (e.g., for a still camera) (348/231)
- FOR 209 ...With storage of additional, non-image information (e.g., audio, time, date) (348/232)
- FOR 210 ...Detachable (348/233)
- FOR 211 ... Electronic zoom (348/240)
- FOR 212 .. Variable magnification (i.e., zoom) (348/358)